



US005868114A

United States Patent [19]

Kamimura et al.

[11] Patent Number: 5,868,114
[45] Date of Patent: Feb. 9, 1999

[54] AIR FLOW RATE CONTROL APPARATUS

5,452,697 9/1995 Sasaki et al. 123/399
5,490,487 2/1996 Kato et al. 123/399
5,517,966 5/1996 Kanazawa et al. 123/399

[75] Inventors: Yasuhiro Kamimura, Hitachinaka;
Yasushi Sasaki, Ibaraki-ken; Sadayuki
Aoki, Takahagi; Kazuo Nagayama,
Hitachinaka, all of Japan

FOREIGN PATENT DOCUMENTS

[73] Assignees: Hitachi, Ltd.; Hitachi Car
Engineering Co., Ltd., both of Japan

0 315 794 A3 5/1989 European Pat. Off. .
0 317 813 A3 5/1989 European Pat. Off. .
0 596 392 A1 5/1994 European Pat. Off. .
34 05 935 A1 5/1985 Germany .
61-8441 1/1986 Japan .
3-50338 3/1991 Japan .
62-35334 8/1994 Japan .
WO 91/02890 3/1991 WIPO .

[21] Appl. No.: 969,708

[22] Filed: Nov. 24, 1997

Related U.S. Application Data

[63] Continuation of Ser. No. 583,794, Jan. 16, 1996, abandoned.

[30] Foreign Application Priority Data

Jan. 17, 1995 [JP] Japan 7-004673
Jan. 19, 1995 [JP] Japan 7-006189

[51] Int. Cl.⁶ F02D 11/10; F16K 31/04

[52] U.S. Cl. 123/399; 251/129.11; 73/117.3;
73/118.2

[58] Field of Search 123/396, 361,
123/399, 403; 251/129.11; 73/116, 117.3,
118.1, 118.2

[56] References Cited

U.S. PATENT DOCUMENTS

4,840,349 6/1989 Peter et al. 251/129.11
5,036,816 8/1991 Mann 123/399
5,074,266 12/1991 Kuhn et al. 123/399
5,094,212 3/1992 Kawaguchi et al. 123/470
5,141,070 8/1992 Hickmann et al. 180/197
5,297,521 3/1994 Sasaki et al. 123/396
5,431,141 7/1995 Kanazawa et al. 123/399

Primary Examiner—Willis R. Wolfe

Attorney, Agent, or Firm—Everson, McKeown, Edwards &
Lenahan, P.L.L.C.

[57] ABSTRACT

A throttle control apparatus for an engine on a vehicle is provided, in which the number of component parts in the position detection means and the driven means is reduced to improve the accuracy in its position control and at the same time an integrated wiring is achieved and connectors are aggregated. The position detection means for detecting the position of a control valve, the driven means for controlling the position of the control valve, the means for processing control signals, an output from the position control means for controlling the position of the control valve are disposed within a sealed space defined by a body supporting a control valve shaft, and a cover. Based on the fact that the number of component parts of the position detection means may be reduced, the mechanical hysteresis and electrical hysteresis may also be reduced to improve the accuracy in controlling the control valve position, and it is possible to aggregate the connectors.

20 Claims, 6 Drawing Sheets

